



D4979-1F FLAT PATTERN BRACKET

D4979-1 BRACKET

NOTES:  
1) MATERIAL: AISI 304/316 STAINLESS STEEL SHEET ANNEALED 2B FINISH, 16 GAUGE (0.063 THICK)  
PER AMS 5513 (304) OR 5524 (316) OR ASTM A240 OR ASME SA240  
REF DART SPEC. M304S16GA  
2) FINISH: PRIME PER QSI 005 4.2.1  
3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED  
4) UNITS: INCHES UNLESS OTHERWISE NOTED  
5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX  
6) IDENTIFICATION: IDENTIFY WITH DART P/N "D4979-1", AGUSTA WESTLAND P/N "TBD", REVISION, BATCH NUMBER AND DATE OF MANUFACTURE,  
USING AN X-TENSION STAMP, PER QSI 044 METHOD 6.2  
7) WEIGHT: 0.05 lbs (0.02 kgs)  
8) UNDIMENSIONED FEATURES CONTROLLED BY CAD MODEL FILE: D4979-1-a.IGES

PRELIMINARY ISSUE

A	NEW ISSUE		DC	13.11.13
REV.	DESCRIPTION		BY	DATE
DESIGN	DC	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA		
DRAWN	DC			
CHECKED	RF	DRAWING NO.		REV. A7
MFG. APPR.	JLM	D4979		SHEET 1 OF 2
APPROVED		TITLE		SCALE
DE APPR.		BRACKET		NTS
DATE	13.11.13	COPYRIGHT © 2013 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.		

